











Feature list:

- · GSM Quad-band
- GPS+GSM+GPRS wireless network
- · High sensitive GPS chipset
- · Real-time tracking
- Built-in GSM&GPS antenna
- Built-in ON/OFF power, wide voltage input range
- Built-in acceleration sensor for vibration alarm
- · Support ACC detection, real-time reporting car status
- Built-in 450mAh battery for alarm when the power supply is disconnected unexpectedly
- · Tele-cut off (petrol/electricity) function
- Check location information via SMS and GPRS(TCP)
- · SOS button for SOS alarm
- · Voice monitor function
- · Built-in CPU, eliminating breakdown automatically
- · Three LED indicators: GPS-blue; GSM-green; Power-red
- · Check location via platform

Specification:

GSM: 850/900/1800/1900 MHz

GPRS: Class12, TCP/ IP build in GSM Module

GPS: MT3326

GSM antenna: built-in guad band

GPS antenna: built-in GPS high gain ceramics patch antenna.

GPS Channels: 20

Tracking sensitivity: -159dBm

Acquisition sensitivity: -144dBm

Locating time cost: Hot start: <2 sec (open sky)

Warm start: <15 sec

Cold start: <38 sec (open sky)

Application environment: Operating temperature: -25°C to +60°C

Operating humidity: 5% to 95% non-condensing

Battery: 3.7vDC/450mAh

Monitoring range: 5M

Working voltage/current: 9-36 vDC/90mA

LED indicator: Three LED indicator: GPS-blue, GSM-green, Power-red

Dimensions: 98.0(L)× 52.0(W)× 15.0(H)mm

Weight: 80g

Certifications: e-mark